

1 SAM ↓



M 108[↗]

TEL/FAX:021-57350280/021-51368588



ˆE a ˆˆ

ˆE ˆˆ ĩ ˆ ƒ ˆ ˆ a Ĝ ˆ ˆ ˆ ˆ ˆ
ˆ ˆE ˆ ˆ ˆ No ˆ
ˆ ˆ Ĝ





α 1 'E~ L b 'Y , 'HNo 'Y b η ' H
A ['HNo i ρ α
≠ 1 z 1 z γ β γ β
α 'Y 'E~ γ β



操作手冊

1	↑		5
1.1			5
1.2			5
1.3	a		5
1.4	a		7
1.5	↑		7
2	η		7
2.1			7
2.2	b η		7
2.3	E [~] b η		7
2.4	k η		8
3 ^{ap}	Đ		9
3.1	↑ ^{ap} :		9
3.2	↑		9
3.3	↑ b ↑		9
3.4			10
4	a		11
4.1	L		11
4.2			11
4.3	a		11
4.4	%		11
4.5	L		12
4.6	G		12
4.7	ĩ k		15
5	ŵ		16

Đ . ↑



操作手冊


1 ↓

1.1

	r	SAM-285	SAM-440	SAM-700					
∞	SAM-440-08	SAM	↓	440	↑ β	↓ β	L/min	08 η	
1 z	↓ β								



4 :



α V ã ‰ DIN7753 PART1 / ISO 4184
ISO 1940-G6.3 VDI2060-Q6.3 ISO 8821 ¶
ρ ¶ ~ κ





3.4 Oil-free scroll air end technical data

Model	Shaft power	Rated pressure	Air displacement	Exhaust interface	Speed	Noise value	Outline size	Weight
	KW	Mpa	L/min	inch	r/min	dB(A)	mm	kg
SAM-285	2.2	0.8	250	PT3/8"	2840	64	270x300x265	15.5
	2.4	1.0	215		2400			
SAM-440	3.75	0.8	410	PT1/2"	3050	65	347x330x295	19.5
	4.4	1.0	355		3000			
SAM-700	5.5	0.8	570	PT3/4"	2950	66	335x381x357	31.5
	6.0	1.0	490		2650			



4. a

4.1 L

w	1	L _{min}	1	±
w	1		±	
	3	i		↓



Å β ¨ 1
v ¨
1 Å Å
1 z 1 1 1 z v ¨ Å 1 z v 1 z v
Å Å

4.5 L

1 z 1 z v 1 Å p 1 z 1
z v 1 z v 1 z 1
Å Å Å p 1 z
Å
G Å ü G Å
β L B ¨
Å Å Å
1 Å

4.6 G

G I ¨ í r. b 1 k G I || n
a n p
G I b Å ¨ ® ¨
1 k v 1 H Ð || p 1 z
p ¨ H Ð 1 Å b ð H
G I k í Ð 1 p
1 G I
% ð
= G I
A γ G 1 ü ¨
1 p



1 1 ĩ Ĝ Ī

ñ 1 z D D ï 1 1 D 1 1

Ĝ Ī ĩ

' 1

' ' 1 ψ 1 γ Ĝ

Ũ №

' Ũ 1 z

1~ o 1 1~

1 r Ĝ Ī

Ĝ Ī 7/8

b D , D ≠

D p || 1 z 1

1 b v

≠ D ~

q D

∞ Ĝ 1

γ 1 ‰ v

Ĝ Ī ĩ

	ρ							
		500	2500	5000	10000	15000	20000	
		2		2	4	6	8	
	v						•	3500h v
			○	•	•	•	•	
┐				○	○	○	○	
			○	○	○	○	○	
					○			
			○	•	•	•	•	
γ				○	•	○	•	
η			○					2500h
		○	•					6
D					○		○	

○ ●



γ $\bar{G}$ $\frac{1}{\gamma}$ $\%$ γ

$\bar{G}$ $\bar{I}$ $\bar{I}$

	$\dot{p}$							
		500	2500	5000	10000	15000	20000	
		2		2	4	6	8	
	γ						•	2500h γ



ĩ k

ı ĩ k

ı

k



DANIEL

THE FUTURE IS NOW

1 G I

8

